



LIFE PAINT

PRODUCT SPECIFICATIONS



WATERPROOFING

1577

FM System Texture Coat

Description: A high build textured intermediate coat composed of specially formulated acrylic resins combined with multi-directional chopped plastic fiber to provide a tough yet flexible coating.

Use: As a textured intermediate coat for the Life Deck "FM System".

Advantages

- * Superior inter-coat adhesion
- * Excellent flexibility
- * Hard and wear resistant
- * Non-water absorptive
- * Asbestos free
- * Wear resistant

Finish: Flat

Package Size: Gallons, 5 Gallons

Color : Gray

Preparation

Seal all cracks in concrete or magnesite with a Life Deck approved caulk, then smooth the crack with FM #1577 Texture Patching Compound.

Using FM reinforcing tape and FM base coat resin, cover large cracks in concrete or seams in plywood and smooth out with FM #1577 Texture Patching Compound.

Primer Requirements

If the surface is either concrete or magnesite, the surface must be primed using FM #1575 Primer at a coverage rate of 200-300 square feet per gallon.

Important weather guidelines:

1. Apply on warm, clear, sunny days.
2. Do not apply under foggy conditions.
3. Do not apply when rain is forecast within 24 hours.
4. Do not apply if temperatures are expected to drop below 50°F within 24 hours.

Clean-up: Soapy water.

Thinning: Do not thin. (If necessary to maintain workability, thin with a small amount of water.)

Texture Coat:

1. Protect all surrounding areas with masking paper.
2. Mix Life Deck FM #1577 Texture Patching Compound thoroughly.
3. Using a roller or an acoustical hopper gun, spray texture at a rate of 80-90 square feet per gallon, depending on desired texture.
4. Allow to dry thoroughly before applying top coat. Under normal drying conditions this should be approximately 4 hours.
5. Optional Step: A few moments after texture coat application while it is still wet, depending on the temperature, the texture can be "knocked down" using a 20" x 5" pool trowel.
6. Scrape and sweep the dried texture surface to remove any sharp or pointed edges.
7. Texture may be rolled on with texture loop or carpet roller. Brush all edges with paint brush. Texture may also be troweled although surface may be more slippery without the orange peel finish. In this case, we advise using the safety coating 15 series as a top coat to minimize slipping.
8. Apply top coat.

WARRANTY: When the warranted product is applied in accordance with label instructions and common sense widely accepted painting practice and procedures, Life Paint will warrant said product against manufacturing defects that might cause premature failure such as blistering, peeling, or unusual wear. Directions are as complete as possible but cannot encompass all conditions, applications, and/or surfaces beyond manufacturer's control. In the event of a warranted failure and upon the presentation of proof of purchase, the remedy will be the provision price for said product. This warranty does not include labor or the costs associated with labor. This warranty may not be transferred or assigned and extends specific legal rights which may vary from state-to-state. No other warranty is expressed or implied.

Technical Information

Type:	Acrylic
Diluent:	Water
Solids Content:	57-60% by weight 51-54% by volume
Viscosity:	>100 KREBS units at 77°F
Flash Point:	>200°F
Maximum V.O.C.:	50 grams per liter

This product contains chemicals known to the State of California to cause cancer, birth defects and reproductive harm. The maximum V.O.C. of this product does not exceed 50 grams/liter. **WARNING!** If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.